

PRODUCT INFORMATION

SEDIMENT FILTER

Sediment filters are used for treating cloudy, dirty or highly turbid waters. The particles are trapped within the media and the clear water passes through. Turbid water may contain organic compounds, clays, metals such as iron and manganese.

Sediment filters

Sediment filters are needed when the water supply is cloudy or turbid. The particles in the water will block plumbing systems, leave unsightly staining, may contain toxic chemicals or bacteria. The easiest way to remove the particles is by passing the water through a media where the particles get stuck and allowing clear water to flow through. The particles can be periodically 'backwashed' away to drain.

Turb 20

Turb 20 has an irregular surface area providing a higher surface area a more complex flow path for a highly efficient removal of suspended matter. This can lead to savings over traditional filter materials such as sand as the equipment can be smaller. Turb 20 is also lighter in weight which reduces backwash flow rate. Turb 20 is slightly more expensive than sand and must be soaked for 24 hours before use.

Turb 5

Turb 5 is very similar to Turb 20 but is slightly heavier. It gives a finer level of filtration making it perfect for those applications where we come across fine suspensions in the water. Turb 5 gives higher flow rates than Turb 20 but being heavier requires a higher backwash flow rate.

Turb 20	10.54	12.52	13.54	14.65	16.65	18.65
Duty Flow cu.m/h	0.6	0.9	1.0	1.2	1.6	2.0
Backwash Flow	1.1	1.8	1.0	2.3	3.4	3.9
Turb 5	10.54	12.52	13.54	14.65	16.65	18.65
Duty Flow cu.m/h	1.6	2.0	2.5	3.0	3.9	5
Backwash Flow	1.6	2.3	2.8	3.2	4.5	5.6



Prosep Filter Services Ltd
Unit G19, River Bank Way,
Lowfields Business Park,
Elland,
West Yorkshire HX5 9DN

Phone: 01422 377367

email:
enquiries@privatewatersupplyservices.co.uk

www.privatewatersupplyservices.co.uk



for all your Private Water Supply requirements